



Trimble RTS573

ROBOTIC TOTAL STATION

ACCURACY FOR EVERYDAY APPLICATIONS

With the Trimble® RTS573 Robotic Total Station contractors can improve efficiency and accuracy for common layout tasks in building construction.

For Everyday Layout

Automate building layout tasks with total confidence. The Trimble RTS573 streamlines layout of curbing, retaining walls, landscape, grade checks, concrete forms, anchor bolts, or utilities. Versatile enough for light topographic projects and as-built data collection, the RTS573 can handle almost any challenge on the job site.

UNSURPASSED TOTAL STATION TECHNOLOGY

Trimble MagDrive™ Servo Technology provides for exceptional speed and accuracy with smooth, silent operation.

Trimble SurePoint™ Technology ensures accurate measurements by automatically correcting for unwanted movement due to wind, sinkage, and other factors.

Trimble MultiTrack™ technology locks on and tracks passive prisms for control measurements and active targets for dynamic measurement, stakeout and grade control.

BUILT FOR CONSTRUCTION

- ▶ For construction applications, you need a measurement solution with optimal speed, accuracy and reliability. With the Trimble DR Plus EDM you have the flexibility to tackle the most demanding projects.
- ▶ Visually mark points, with high precision, using the Class 2 Laser Pointer.
- ▶ Automatic Servo Focus sets the optical focus for quick manual aiming when laying out points in DR mode.
- ▶ Combine with Trimble Field Link software running on the Trimble Field Tablet to optimize your accuracy and productivity.

Key Features

- ▶ MagDrive technology for maximum speed and efficiency
- ▶ MultiTrack technology offers the choice between passive and active tracking
- ▶ Long range EDM to collect specific job site conditions



Trimble RTS573 ROBOTIC TOTAL STATION

PERFORMANCE

Horizontal angle measurement accuracy (standard deviation based on DIN 18723) 3" (0.9 mgon)
 Vertical angle measurement accuracy (standard deviation based on DIN 18723) 2" (0.6 mgon)
 Angle display (least count) 0.1" (0.01 mgon)

Distance measurement

Typical Accuracy	50 m (164 ft)	100 m (328 ft)	200 m (656 ft)	300 m (984 ft)
Prism mode Standard Tracking	2 mm (5/64") 4 mm (5/32")	3 mm (1/8") 5 mm (13/64")	4 mm (5/32") 6 mm (15/64")	6 mm (15/64") 7 mm (9/32")
DR mode Standard Tracking	2 mm (5/64") 4 mm (5/32")	3 mm (1/8") 4 mm (5/32")	4 mm (5/32") 5 mm (13/64")	5 mm (13/64") 6 mm (15/64")

Measuring time

Prism mode
 Standard 1.2 s
 Tracking 0.4 s
 DR mode
 Standard 1.5 s
 Tracking 0.4 s

Range (under standard clear conditions^{1,2})

Prism mode
 1 prism 2,500 m (8,202 ft)
 Shortest range 0.2 m (0.7 ft)

DR mode

	Extended Mode	Good (Good visibility, low ambient light)	Normal (Normal visibility, moderate sunlight, some heat shimmer)	Difficult (Haze, object in direct sunlight, turbulence)
White card (90% reflective) ³	2,200 m (7,218 ft)	1,300 m (4,265 ft)	1,300 m (4,265 ft)	1,200 m (3,937 ft)
Gray card (18% reflective) ³	1,000 m (3,280 ft)	600 m (1,968 ft)	600 m (1,968 ft)	550 m (1,804 ft)

Shortest range 1.0 m (3.3 ft)

EDM SPECIFICATIONS

Light source
 EDM DR Plus Laser Class 1
 Tracker Laser Class 1

Laser pointer Laser class 2
 Beam divergence
 Horizontal 2 cm/50 m (0.066 ft/164 ft)
 Vertical 4 cm/100 m (0.13 ft/328 ft)
 Atmospheric correction -130 ppm to 160 ppm continuously

GENERAL SPECIFICATIONS

Leveling
 Circular level in tribrach 8/2 mm (8/0.007 ft)
 Automatic level compensator
 Type Centered dual-axis
 Accuracy 0.5" (0.15 mgon)
 Range ±5.4' (±100 mgon)
 Servo system MagDrive servo technology, integrated servo/angle sensor; electromagnetic direct drive
 Rotation speed 115 degrees/s (128 gon/s)
 Rotation time Face 1 to Face 2 2.6 s
 Positioning speed 180 degrees (200 gon) 2.6 s
 Clamps and slow motions Servo-driven, endless fine adjustment
 Centering
 Centering system Trimble 3-pin
 Optical plummet Built-in optical plummet
 Magnification/shortest focusing distance 2.3x/0.5 m to infinity (1.6 ft to infinity)
 Telescope
 Magnification 30x
 Aperture 40 mm (1.57 in)
 Field of view at 100 m (328 ft) 2.6 m at 100 m (8.5 ft at 328 ft)
 Shortest focusing distance 1.5 m (4.92 ft) to infinity
 Illuminated crosshair Variable (10 steps)
 Autofocus Standard
 Tracklight built in Not available in all models
 Operating temperature -20° C to +50° C (-4° F to +122° F)
 Dust and water proofing IP55
 Humidity 100% condensing
 Power supply
 Internal battery Rechargeable Li-Ion battery 10.8V, 6.5Ah, 70Wh
 Operating time⁴
 One internal battery Approx. 6.5 hours
 Three internal batteries in multi-battery adapter Approx. 18 hours
 Robotic holder with one internal battery 13.5 hours
 Operating time with video robotic⁴
 One battery 5.5 hours
 Three batteries in multi-battery adapter 17 hours
 Weight
 Instrument (Servo/Autolock[®]) 5.15 kg (11.35 lb)
 Instrument (Robotic) 5.25 kg (11.57 lb)
 Trimble CU controller 0.4 kg (0.88 lb)
 Tribrach 0.7 kg (1.54 lb)
 Internal battery 0.35 kg (0.77 lb)
 Trunnion axis height 196 mm (7.71 in)
 Communication USB, Serial, Bluetooth¹⁵
 Security Dual-layer password protection

ROBOTIC RANGE

Autolock and Robotic range²
 Passive prisms 500–700 m (1,640–2,297 ft)
 Trimble MultiTrack Target 800 m (2,625 ft)
 Autolock pointing precision at 200 m (656 ft) (standard deviation)²
 Passive prisms <2 mm (0.007 ft)
 Trimble MultiTrack[™] Target <2 mm (0.007 ft)
 Shortest search distance 0.2 m (.65 ft)
 Search time (typical)⁶ 2–10 s

- Standard clear: No haze. Overcast or moderate sunlight with very light heat shimmer.
- Range and accuracy depend on atmospheric conditions, size of prisms and background radiation.
- Kodak Gray Card, Catalog number E1527795.
- The capacity in -20 °C (-5 °F) is 75% of the capacity at +20 °C (68 °F).
- Bluetooth type approvals are country specific. Contact your local Trimble Authorized Distribution Partner for more information.
- Dependent on selected size of search window.



Specifications subject to change without notice.

Contact your local Trimble Authorized Distribution Partner for more information

TRIMBLE FTG
 116 Inverness Drive East, Suite 210
 Englewood, CO 80112
 Phone: 1-800-234-3758

